



# IES SAP4D-Honda CANBUS Active Parking Sensor

## INTRODUCTION:

**IES SAP4D-HONDA** is a CANBUS active parking sensor system which is designed with the latest ultra-sensing technology. The sensors are with built-in PCB sensor and with plug and play socket. The parking system is with audible beeps if objects are detected to assist the driver in parking and reversing the vehicle. IES SAP4D-Honda CANBUS active parking is with Honda OBD socket which is compatible with selected Honda models vehicle.

## DETECTION DISTANCE AND BUZZER SOUND:

- 0.00 meter - 0.45 meter = The buzzer keep beeping
- 0.46 meter - 0.90 meter = The buzzer continuous beeping
- 0.91 meter - 1.50 meter = The buzzer intermittent beeping

## DETECTION ANGLE:

- Left and Right = 120°
- Up and Down = 60°



## IES HX2554D ACTIVE PARKING SENSOR SPECIFICATION:

- Rated Voltage = DC 12V
- Working Voltage = DC 9.6V – 15V

## BUZZER SPECIFICATION:

- Rated Voltage = DC 5V
- Working Voltage = DC 8V – DC 16V
- Buzzer Volume = 105dB

SUPERCODE TECHNOLOGY (M) SDN. BHD.

C1-01-34 JALAN SR 1/9 SEKSYEN 9 TAMAN SERDANG RAYA 43300 SERI KEMBANGAN SELANGOR DARUL EHSAN.

[www.caralarm.com.my](http://www.caralarm.com.my)